



# HIGH QUALITY AND LOW MAINTENANCE

The Ultrafiltration System from Antunes helps improve the quality of drinking water throughout operation, decreasing the frequency of maintenance issues that can arise due to poor water quality.

The UFL systems feature an ultrafiltration cartridge that substantially reduces particles from the water. The system is self-cleaning, which extends the life of the ultrafilter and allows it to operate with little user intervention. With a small footprint, these systems have added flexibility for easy installation.



### High Quality Water

From the combination of filtration technologies



### Reliability

Antunes water systems are subject to strict quality assurance standards



### Superior Filtration

The system features a .015 micron ultrafilter that substantially reduces particles in the water

Model: UFL Series

# Ultrafiltration System | UFL



Systems tested and certified by NSF International against NSF/ANSI:

Standard No. 42: Aesthetic Effects Nominal Particulate Reduction Class I.

Standard No. 53: Health Effects Cyst Reduction Turbidity Reduction as verified and substantiated by test data.

## Features:

- Simple, compact and effective design
- Ultrafiltration reduces particles to 0.015 microns
- Self-cleaning capabilities extends the life of the ultrafilter
- Operation simplicity
- Several sizes available to meet various flow rates

NOTE: The Flush Tank Kit (P/N 7000472) is highly recommended to improve the flushing function and extend the life of the ultrafilter.

NOTE: Additional taste and odor and scale reduction systems are also available.

## UFL

### Dimensions and Weight

Model & Mfg. No.	Max Flow Rate	UF Length	Inlet	Outlet	Drain	Width	Depth	Height	Operating Weight	Shipping Weight
UFL-510 9710125	5.2 gpm* (19 lpm)	10" (25 cm)	3/4" FNPT	3/4" FNPT	3/4" FNPT	12" (30.5 cm)	6 1/4" (19 cm)	23" (58 cm)	17 lbs. (7.7 kg)	19 lbs. (8.6 kg)
UFL-520 9710126	7.9 gpm* (29.1 lpm)	20" (51 cm)	3/4" FNPT	3/4" FNPT	3/4" FNPT	12" (30.5 cm)	6 1/4" (19 cm)	30" (76 cm)	23 lbs. (10.4 kg)	23 lbs. (10.4 kg)
UFL-540 9710124	15 gpm* (57 lpm)	40" (102 cm)	3/4" FNPT	3/4" FNPT	3/4" FNPT	12" (30.5 cm)	6 1/4" (19 cm)	49" (124 cm)	42 lbs. (19.1 kg)	33 lbs. (15 kg)

\*NSF certified at 5.2 gpm (19 lpm).

\*\*NSF certified at 7.9 gpm (29.1 lpm).

\*\*\*NSF certified at 13 gpm (49.2 lpm).

## Replacement Cartridges

Model & Mfg. No.	Max Flow Rate
7001915	L-510 for use in UFL-510
7001917	L-520 for use in UFL-520
7001916	L-540 for use in UFL-540

## Specifications:

- Maximum Operating Pressure: 100 psig (690 kPa)
- Maximum Operating Temperature: 104°F (40°C)
- Nominal Pore Size: .015 microns
- pH Range: 3 to 10
- MWCO: 100 kD.
- Volts: 100 to 240
- Watts: 10
- Amps: 0.08
- Includes plug adapters for US, Europe, Australia & UK